



13.91 [0.548]
(Insulation Area)
15.01 [0.591]

271.27±0.3 [10.680±0.012]

251.07 [9.885]

6.29 [0.248]
(Insulation Area)

248.87 [9.798](ACTIVE AREA)

(7.39 [0.291])

9.17 [0.361]
(Insulation Area)

8.07 [0.318]
(Insulation Area)

UL

UR

110±1 [4.331±0.039]

187.4 [7.378](ACTIVE AREA)

189.6 [7.465]
(Insulation Area)

205.74±0.3 [8.100±0.012]

- PART No. LABEL
- LOT LABEL

2-R2

PART No.
FST-121C

PIN ASSIGNMENT

- 1 — UR
- 2 — LR
- 3 — SENSE
- 4 — UL
- 5 — LL

TOLERANCE=±0.5mm(0.02in)
EXCEPT WHERE INDICATED
UNIT=mm[inch]

1	ITO FILM (ANTI-GLARE)
2	ITO GLASS
3	TAIL
4	REINFORCEMENT FILM
5	STIFFENER
6	TAIL PROTECTION TAPE
7	ADHESIVE SHEET
8	CONNECTOR (AMP:487526-4) PIN CONTACT (AMP:487406-9)

PART No. LABEL
FST-T121C110A

LOT LABEL

0.5 [0.020]

0.5 [0.020]

2.1±0.083±0.008

9.17 [0.361]
(Insulation Area)

8.07 [0.318]
(Insulation Area)

PART No.	DATE
FST-T121C110A	May. 02, 2013
TYPE	DMC Co., Ltd.
STANDARD TOUCHSCREEN DIMENSIONAL DRAWING	